

SERIES ESP GORDON-PIATT BURNER SELECTION



Boiler Model	Burner Model Gas/Oil-PA	Burner Model Gas/Oil-AA	Max. Input Gas MBH	Max. Input Oil#2 GPH	Max. Input Oil#6 GPH
ESP-070	S10.9-XX-10	F10-XX-15	2929	21	20
ESP-080	S10.9-XX-10	F10-XX-15	3348	24	23
ESP-090	S10.1-XX-30	F10.1-XX-30	3766	27	25
ESP-100	S10.1-XX-30	F10.1-XX-30	4185	30	28
ESP-125	S12-XX-50	F12.9-XX-30	5230	38	35
ESP-150	S12.1-XX-50	F12-XX-50	6276	45	42
ESP-175	S12.1-XX-50	F12.1-XX-50	7323	52	49
ESP-200	S14.9-XX-30	F14.9-XX-50	8369	60	56
ESP-250	S14-XX-50	F14-XX-50	10461	75	70
ESP-300	S16-XX-75	F16-XX-75	12554	90	84
ESP-350	S16-XX-75	F16-XX-75	14645	105	98
ESP-400	F16.1-XX-100	F16.1-XX-100	16738	120	112
ESP-450	F18.9-XX-150	F18.9-XX-150	18830	135	126

Notes:

1. NA – Not Available.
2. PA – Pressure Atomizing.
3. AA – Air Atomizing.
4. Gordon-Piatt Burners Nomenclature – ABB.B-XX-CC: A – Burner Type (Series), BB.B – Burner Size, XX - Fuel (G – Gas, O – Fuel Oil, GO Combination Gas/Oil), CC – Blower Motor HP.

EASCO Boiler Corp.

1175 Leggett Avenue, Bronx NY 10474 USA

Ph: 718-378-3000 • Fax: 718-378-4560 • E-mail: webmaster@easco.com

Page 1 of 1

ESPGPBS01GM