

SERIES SM5 GORDON-PIATT BURNER SELECTION



Boiler Model	Burner Model Gas/Oil-PA	Burner Model Gas/Oil-AA	Max. Input Gas MBH	Max. Input Oil#2 GPH	Max. Input Oil#6 GPH
SM5-020	S6.1-XX-03	N/A	816	5.8	NA
SM5-025	S6.2-XX-05	N/A	1020	7.3	NA
SM5-030	S8.8-XX-03	N/A	1225	8.7	NA
SM5-035	S8.9-XX-05	N/A	1429	10.2	NA
SM5-040	S8.9-XX-05	N/A	1633	11.7	NA
SM5-050	S8.1-XX-10	N/A	2041	14.6	NA
SM5-060	S8.3-XX-20	N/A	2449	17.5	NA
SM5-060SP	S8.2-XX-15	N/A	2449	17.5	NA
SM5-070	S10.9-XX-10	N/A	2857	20.4	NA
SM5-080	S10-XX-20	N/A	3266	23.3	NA
SM5-090	S10.1-XX-30	N/A	3674	26.2	NA
SM5-100	S10.2-XX -50	N/A	4082	29.2	NA
SM5-125	S12-XX-50	N/A	5102	36.4	NA
SM5-150	S12.1-XX-50	N/A	6123	43.7	NA

Notes:

1. NA – Not Available.
2. PA – Pressure Atomizing.
3. AA – Air Atomizing.
4. Gordon-Piatt Burners Nomenclature – ABB.B-XX-CC: A – Burner Type (Series), BB.B – Burner Size, XX - Fuel (G – Gas, O – Fuel Oil, GO Combination Gas/Oil), CC – Blower Motor HP.

EASCO Boiler Corp.

1175 Leggett Avenue, Bronx NY 10474 USA

Ph: 718-378-3000 • Fax: 718-378-4560 • E-mail: webmaster@easco.com

Page 1 of 1

SM5GPBS01GM